



N.	COMPONENT	MATERIAL	QUANT.										
1	BODY	EN 1561 EN-GJL-250	1										
2	PLUG (2VGG)	EN 1561 EN-GJL-250 (Dn 1/2"-4")	1	DN	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"	2 1/2"	3"	4"
	PLUG (2VGB)	EN 1982 Cu Zn Pb2 Ni1 Al Fe-C (CC7535) (Dn 1/2"-4")		L (mm)	82	92	102	120	135	160	230	250	290
3	GLAND	EN 1561 EN-GJL-250	1	q (mm)	15	16	18	22	24	27	32	36	52
4	PACKING	SYNTHETIC PACK, GRAPHITED, LUBRICATED	1	hm (mm)	90	95	100	120	130	145	180	190	230
5	STUD	AVP	2	weight (Kg)	1	1.5	2	2.7	3.7	6	11	15	25
6	NUT	Fe	2										
6-7	SCREW WITH NUT (ONLY 2VGG: ON REQUEST FOR 2VGB)	Fe	1										

DIMENSIONS in mm GENERAL TOLERANCES ISO 2768-m	<b>THREADED PLUG COCK WITH GLAND 2-WAY          NP 10-16</b>		
	CODE 2VGG/2VGB	DWG. NO. 103	REV. 00
	CATEGORY RM FIL		