



**NO STEP!**

TECHNICALS

d	W (Kg)	df (mm)	sc (mm)	q (mm)	hm (mm)
Dn 20	2.7	105	47.5	16	98
Dn 25	3.5	115	57.5	18	105
Dn 32	5	140	60	22	120
Dn 40	7	150	70	24	130
Dn 50	10	165	80	27	145
Dn 65	15	185	115	32	180
Dn 80	19	200	130	36	190
Dn 100	30	220	160	50	230
Dn 125	57	250	177.5	61	300
Dn 150	78	285	200	66	330

OPERATING TEMPERATURE:  
0-120° FOR GB; 0-200° FOR GG.

SUITABLE FOR WATER AND  
VISCIOUS/ EROSIIVE FLUIDS.

LOW HEAD LOSSES.

N.	COMPONENT	MATERIAL	DIS. N./REV	QUANT.
1	BODY	EN 1561 EN-GJL-250		1
2	PLUG (2VGG)	EN 1561 EN-GJL-250 (Dn 20-100)		1
	PLUG (2VGB)	EN 1982 Cu Zn Pb2 Ni1 Al Fe-C (CC753S) (Dn 20-100) EN 1982 Cu Zn 5 Pb 5 Sn 5 (Dn 125-150)		
3	GLAND	EN 1561 EN-GJL-250		1
4	PACKING	SYNTHETIC PACK, GRAPHITED, LUBRICATED		1
5	SCREW	Fe		2 4 (Dn 125-150)
6-7	SCREW WITH NUT (ONLY 2VGG- 2VGB100-2VGB125-2VGB150; ON REQUEST FOR OTHERS)	Fe		1

DIMENSIONS in mm  
GENERAL TOLERANCES  
ISO 2768-m

PLUG COCK WITH GLAND 2-WAY  
NP 10-16

DRW. N. REV.  
101 00

CATEGORY RM | COD. 2VGG/2VGB